

# LED CLE/CLLE

Convenient replacement for CFL and incandescent lamps with E14 base



CLE E14

CLLE E14



### APPLICATIONS

- To replace conventional candle lamps in fittings with E14 lampholders

### TECHNICAL DETAILS

- SMD LED
- Rated life: 25,000 hours

### CONSTRUCTION

- Plastic coated aluminium housing
- Built-in constant current LED driver included

### OPTIONS

- **Dimming:** Fixed output as standard, but mains dimmable versions are available for use with suitable phase-cutting dimmers. If required, add suffix MD when ordering.
  - 110-240V: Standard version
  - 220-240V: Dimmable version

Model	Colour temp.	Lumens	Input	CRI	PF
LED CLE 3W	2700K/3000K/4000K/6500K	240lm	110-240V	>80	>0.7
LED CLE 4W	2700K/3000K/4000K/6500K	310lm	110-240V	>80	>0.7
LED CLE 5W	2700K/3000K/4000K/6500K	370lm	110-240V	>80	>0.7
LED CLE DIM 5W	2700K/3000K/4000K/6500K	370lm	220-240V	>80	>0.7
LED CLL E 3W	2700K/3000K/4000K/6500K	240lm	110-240V	>80	>0.7
LED CLL E 4W	2700K/3000K/4000K/6500K	310lm	110-240V	>80	>0.7
LED CLL E 5W	2700K/3000K/4000K/6500K	370lm	110-240V	>80	>0.7
LED CLL E DIM 5W	2700K/3000K/4000K/6500K	370lm	220-240V	>80	>0.7

