

LED G4/G9-II

High efficiency LED lamps to replace tradition laps with G4 or G9 bases



G4 1W
(Class III)



G4 2W
(Class III)



G4 3W
(Class III)



G9-II 3W
(Class II)



APPLICATIONS

- Suitable for use in fittings with G4 or G9 lampholders

OPTIONS

- **Dimming:** Fixed output as standard, but mains dimmable versions are available for use with suitable phase-cutting dimmers. If required, add suffix MD when ordering

CONSTRUCTION

- Polycarbonate housing and cover
- Built-in constant current LED driver included

TECHNICAL DETAILS

- SMD LEDs
- Rated life: 30,000 hours

Model	Colour temp.	Lumens	Input	Dimmable	CRI	PF	Beam angle
LED G4 1W	2700K/3000K/6000K	110 lm	AC/DC12V	NO	>80	>0.5	180°/240°/300°
LED G4 1W	2700K/3000K/6000K	90 lm	DC12V	YES	>80	>0.5	180°/240°/300°
LED G4 2W	2700K/3000K/6000K	200 lm	AC/DC12V	NO	>80	>0.5	180°/240°/300°
LED G4 2W	2700K/3000K/6000K	180 lm	DC12V	YES	>80	>0.5	180°/240°/300°
LED G4 3W	2700K/3000K/6000K	280 lm	AC/DC12V	NO	>80	>0.5	180°/240°/300°
LED G9-II 3W	2700K/3000K/6000K	260 lm	220-240V	NO	>80	>0.8	180°/240°/300°

