

NBTLED T5P

Plastic battens



APPLICATIONS

- General commercial lighting
- Stores
- Cove lighting

TECHNICAL DETAILS

- SMD LEDs
- Rated life: 30,000 hours

CONSTRUCTION

- Plastic housing
- Opal polycarbonate diffuser
- Built-in LED driver included
- Linkable
- Plugs, middle connectors, end caps and installation accessories included

NOTES

- Maximum connection
•10pcs for all wattages




OPTIONS

- Built-in switch version available, use suffix S
- **Jumper cable:** Order this as a separate item




Model	Watts	Colour temp.	Lumens	CRI	PF
Standard version					
NBTLED T5P4/03	4W	3000K/4000K/6500K	400 lm	>70	>0.5
NBTLED T5P7/06	7W	3000K/4000K/6500K	700 lm	>70	>0.5
NBTLED T5P10/09	10W	3000K/4000K/6500K	1,000 lm	>70	>0.5
NBTLED T5P14/12	14W	3000K/4000K/6500K	1,400 lm	>70	>0.5
Switch version					
NBTLED T5PS4/03	4W	3000K/4000K/6500K	400 lm	>70	>0.5
NBTLED T5PS7/06	7W	3000K/4000K/6500K	700 lm	>70	>0.5
NBTLED T5PS10/09	10W	3000K/4000K/6500K	1,000 lm	>70	>0.5
NBTLED T5PS14/12	14W	3000K/4000K/6500K	1,400 lm	>70	>0.5

Accessories	Description
Jumper cable	NBTLED T5P Jumper Cable (2 wires 20cm long)



NBTLED T5D7/06 160°



NBTLED T5D14/12 160°