

NDLLED915 series

Downlight with step-dimming or colour temperature selection



Semi-white



Sanded Silver



Brass



APPLICATIONS

- Residential lighting
- Bedrooms
- Corridors and living rooms

OPTIONS

- **Bezel colours:** Choice of
 - Semi-white (SW)
 - Sanded Silver (SS)
 - Brass (BS)
- **Dimming and CCT selection**
 This downlight can be controlled via the mains switch to deliver either step-dimming or a choice of colour temperatures:
 - Step-dimming (ST). Switching the mains switch on/off quickly causes the light source to step between 100%, 50% and 20% output

CONSTRUCTION


- Aluminium body
- Integrated driver

TECHNICAL DETAILS



- SMD LEDs
- Rated life: 30,000 hours

- Colour selection (CCT). Switching the mains switch on/off quickly causes the light to step between 3000K, 4000K and 5700K
- Note that each version offers either step-dimming or colour selection. If ordering step-dimming then a fixed CCT has to be specified; if ordering a CCT selectable version then step-dimming is not available

Model	Colour temp.	Lumens	CRI	PF
NDLLED91525 4W	3000K/4000K/5700K	240 lm	>80	>0.5
NDLLED9153 6W	3000K/4000K/5700K	360 lm	>80	>0.5
NDLLED91535 8W	3000K/4000K/5700K	480 lm	>80	>0.95
NDLLED9154 10W	3000K/4000K/5700K	650 lm	>80	>0.95



Watts	A	B	Cut-out
4W	Ø94	56	Ø75
6W	Ø104	54	Ø85
8W	Ø114	59	Ø95
10W	Ø140	66	Ø120



NLED9153 6W 90°

NLED91535 8W 90°