

NELED4201

Low wattage in-ground light



APPLICATIONS

- Outdoor decorative lighting
- Paths
- Squares and parks

TECHNICAL DETAILS

- CREE LEDs
- Rated life: 30,000 hours

CONSTRUCTION

- Die-cast aluminium housing
- 316 brushed stainless steel bezel
- Tempered glass cover 5mm thick
- PVC mounting sleeve
- LED driver are not included
- Weight limit: 113kg on area Ø10mm
- Complete with a IP67 cable gland, and pre-wired with 2x1.00mm² H05RN wire

OPTIONS

- **Driver:** Choice of separate DC 24V IP65 driver (separate driver not included)
- **Connector:** Choice of two types of IP67 connector, straight (type I) or T (type T)



Model	LED Chip	Watts	Colour temp.	Lumens	CRI
NELED4201	1x0.5W	1W	3000K	10 lm	>80
NELED4201	1x0.5W	1W	6000K	11 lm	>80
NELED4201R	1x0.5W	1W	3000K	10 lm	>80
NELED4201R	1x0.5W	1W	6000K	11 lm	>80

Accessories		Driver
CNI02 2pin type I IP67 connector	CNT02 2pin type T IP67 connector	NLED-DV110* (see page 127)
CNI03 3pin type I IP67 connector	CNT03 3pin type T IP67 connector	
CNI04 4pin type I IP67 connector	CNT04 4pin type T IP67 connector	
CNI05 5pin type I IP67 connector	CNT05 5pin type T IP67 connector	

