

NELED4212

Side light output IP67 in-ground light



NELED4212A



NELED4212B



NELED4212D



APPLICATIONS

- Outdoor decorative lighting
- Paths
- Squares and parks

TECHNICAL DETAILS

- SMD LEDs
- Rated life: 30,000 hours

CONSTRUCTION

- Die-cast aluminium housing
- 316 brushed stainless steel bezel
- Tempered glass cover 8mm thick
- PVC mounting sleeve
- Weight limit: 2,000kg
- LED driver included with 110-240V versions only
- Complete with a IP67 cable gland, and pre-wired with 2x1.00mm² H05RN wire (DC24V) or 3x1.00mm² H05RN wire (110-240V)

OPTIONS

- **Driver:** Choice of separate DC 24V IP65 driver (separate driver not included)
- **Connector:** Choice of two types of IP67 connector, straight (type I) or T (type T)



Model	LED Chip	Watts	Colour temp.	Lumens	CRI
NELED4212A	6x0.5W SMD5630	3W	3000K	8 lm	>80
NELED4212B	6x0.5W SMD5630	3W	3000K	10 lm	>80
NELED4212D	6x0.5W SMD5630	3W	3000K	15 lm	>80
Accessories		Driver			
CNI02 2pin type I IP67 connector	CNT02 2pin type T IP67 connector	NLED-DV110* (see page 127)			
CNI03 3pin type I IP67 connector	CNT03 3pin type T IP67 connector				
CNI04 4pin type I IP67 connector	CNT04 4pin type T IP67 connector				
CNI05 5pin type I IP67 connector	CNT05 5pin type T IP67 connector				

