

NFLED4012 NFLED4013

Landscape high power flood lights




NFLED4012



NFLED4013




NFLED4012



Covier Beam LUX	Beam Width	
	V	H
2m	0.7m	0.7m
4m	1.40m	1.40m
6m	2.10m	2.10m
8m	2.80m	2.80m
10m	3.50m	3.50m
12m	4.20m	4.20m


Vert. Spread: 19.7 Horiz. Spread: 19.3

NFLED4013



Covier Beam LUX	Beam Width	
	V	H
2m	1m	1m
4m	2m	2m
6m	3m	3m
8m	4m	4m
10m	5m	5m
12m	6m	6m


Vert. Spread: 28.2 Horiz. Spread: 27.9




NFLED4012
Windage: 0.008m²
Weight: 0.9kg



Spike
(Not included)




NFLED4013
Windage: 0.017m²
Weight: 1.7kg




Spike
(Not included)

Model	Input	LED Chip	Watts	Colour temp.	Lumens	CRI	Beam angle
NFLED4012	DC24	3x2W	6W	3000K	380lm	>80	15°, 30°
NFLED4012	DC24	3x2W	6W	6000K	460lm	>80	15°, 30°
NFLED4012	110-240V	3x2W	7W	3000K	380lm	>80	15°, 30°
NFLED4012	110-240V	3x2W	7W	6000K	460lm	>80	15°, 30°
NFLED4013	DC24	6x2W	13W	3000K	760lm	>80	15°, 30°
NFLED4013	DC24	6x2W	13W	6000K	890lm	>80	15°, 30°
NFLED4013	110-240V	6x2W	13.5W	3000K	760lm	>80	15°, 30°
NFLED4013	110-240V	6x2W	13.5W	6000K	890lm	>80	15°, 30°

Accessories	Driver
spike 210	NLED-DV110* (see page 127)



NFLED4012



NFLED4013