

NFLED4014

Landscape high power flood lights



NFLED4014



APPLICATIONS

- Lawns and gardens
- Paths
- Sculptures

TECHNICAL DETAILS

- NICHIA LED
- Rated life: 30,000 hours

OPTIONS


- **Driver:** Choice of the built-in 110-240V driver or separate DC 24V IP65 driver (separate driver not included)



CONSTRUCTION

- Die-cast aluminium housing
- Power coated aluminium bracket
- Tempered glass 4mm thick
- LED driver included with 110-240V versions only
- Mounting spike not include
- 20V DC, driver not included. please refer to the driver section
- Choice of three finishes:
 - Black (similar to RAL 7021)
 - Dark grey (similar to RAL 7037)
 - Light grey (similar to RAL 7023)

NFLED4014




Center Beam LUX	Beam Width V	H
6177.67LUX	0.2m	0.2m
1544.42LUX	0.5m	0.5m
686.41LUX	0.7m	0.7m
386.10LUX	1.0m	1.0m
247.11LUX	1.20m	1.20m
171.60LUX	1.40m	1.40m

Vert Spread 6.9 Horiz Spread 6.7

cell: nvc
 - C180 - C201

Model	Input	LED Chip	Watts	Colour temp.	Lumens	CRI	Beam angle
NFLED4014	DC24	6x3W	18W	3000K	1600lm	>80	15°, 30°
NFLED4014	DC24	6x3W	18W	6000K	1800lm	>80	15°, 30°
NFLED4014	110-240V	6x3W	18W	3000K	1600lm	>80	15°, 30°
NFLED4014	110-240V	6x3W	18W	6000K	1800lm	>80	15°, 30°

Accessories	Driver
spike 308	NLED-DV110* (see page 127)



NFLED4014
 Windage: 0.025m²
 Weight: 2.4kg



Spike
 (Not included)

