

## NLED912 series

Downlight with aluminium or polycarbonate bezel



NLED912\* (Polycarbonate bezel)



NLED912\*L (Aluminium bezel)



### APPLICATIONS

- Residential lighting
- Retail stores
- Shopping malls

### OPTIONS


- **Bezel material:** Choice of semi-white polycarbonate as standard, or sanded silver aluminium (add suffix L)
- **Sizes:**
  - Fittings with polycarbonate bezel are available in seven wattages. Note that the 8W version is available in two sizes as listed below
  - Fittings with aluminium bezel (suffix L) are available in four wattages. The 8W version is available in one size only

### CONSTRUCTION

- Aluminium + polycarbonate housing
- PC heat sink
- Cream white powder coated finish
- Frosted polycarbonate diffuser
- Aluminium or polycarbonate bezel
- Integrated driver


### TECHNICAL DETAILS

- SMD LEDs
- Rated life: 30,000 hours



NLED912\*


Watts	A	B	Cut-out
4W	Ø94	59	Ø75
6W	Ø104	60	Ø85
8W	Ø107	65	Ø95
8W/10W	Ø132	71	Ø120
12W	Ø180	75	Ø165
15W	Ø188	81	Ø175
20W	Ø220	87	Ø200




NLED912\*L

Watts	A	B	Cut-out
4W	Ø94	57	Ø75
6W	Ø104	57	Ø85
8W	Ø115	67	Ø95
10W	Ø140	72	Ø120

Model	Colour temp.	Lumens	CRI	PF
<b>Polycarbonate bezel</b>				
NLED91225 4W	3000K/4000K/5700K	250 lm	>80	>0.5
NLED9123 6W	3000K/4000K/5700K	360 lm	>80	>0.5
NLED91235 8W	3000K/4000K/5700K	480 lm	>80	>0.9
NLED9124 8W	3000K/4000K/5700K	480 lm	>80	>0.9
NLED9124 10W	3000K/4000K/5700K	600 lm	>80	>0.9
NLED9125 12W	3000K/4000K/5700K	720 lm	>80	>0.9
NLED9126 15W	3000K/4000K/5700K	850 lm	>80	>0.9
NLED9128 20W	3000K/4000K/5700K	1,200 lm	>80	>0.9
<b>Aluminium bezel</b>				
NLED91225L 4W	3000K/4000K/5700K	220 lm	>80	>0.5
NLED9123L 6W	3000K/4000K/5700K	330 lm	>80	>0.8
NLED91235L 8W	3000K/4000K/5700K	450 lm	>80	>0.8
NLED9124L 10W	3000K/4000K/5700K	550 lm	>80	>0.9



NLED91225 4W 90°



NLED9125 12W 90°