

NLED950 E series NLED951 E series

A range of economical IP44 downlights



NLED950*E



NLED951*E
(Recessed glare proof cover)



APPLICATIONS

- Kitchens and washrooms
- Corridors and living areas in homes and small commercial projects

TECHNICAL DETAILS


- SMD LEDs
- Rated life: 30,000 hours
- IP44 front face - suitable for most areas in kitchens, toilets and washrooms
- Push-fit (screwless) terminal block for fast installation
- Terminal block cover with built-in strain relief

CONSTRUCTION


- Body made from plastic coated aluminium
- Body colour: White
- Nano-coated internal reflector for maximum efficiency
- Opal diffuser
- Integrated non-dimmable driver
- Available in five sizes and 10 wattages as listed below: 3 inch, 4 inch, 5 inch, 6 inch and 8 inch

OPTIONS


- Choice of 3000K, 4000K or 5700K colour temperatures




NLED950*E			
Watts	A	B	Cut-out
5W/7W	Ø95	58	Ø68-80
8W/10W	Ø113	59	Ø90-102
12W/14W	Ø145	66	Ø120-130
14W/17W	Ø174	69	Ø145-155
20W/25W	Ø244	85	Ø195-210



NLED951*E			
Watts	A	B	Cut-out
5W/7W	Ø92	64	Ø68-80
8W/10W	Ø113	73	Ø90-102
12W/14W	Ø145	75	Ø120-130
14W/17W	Ø174	79	Ø145-155
20W/25W	Ø244	95	Ø195-210



NLED9503E 7W



NLED9504E 10W

Model	Colour temp.	Lumens	CRI	PF
NLED9503E/NLED9513E 5W	3000K/4000K/5700K	460 lm	>80	>0.5
NLED9503E/NLED9513E 7W	3000K/4000K/5700K	650 lm	>80	>0.5
NLED9504E/NLED9514E 8W	3000K/4000K/5700K	700 lm	>80	>0.5
NLED9504E/NLED9514E 10W	3000K/4000K/5700K	890 lm	>80	>0.9
NLED9505E/NLED9515E 12W	3000K/4000K/5700K	1,150 lm	>80	>0.9
NLED9505E/NLED9515E 14W	3000K/4000K/5700K	1,300 lm	>80	>0.9
NLED9506E/NLED9516E 14W	3000K/4000K/5700K	1,330 lm	>80	>0.9
NLED9506E/NLED9516E 17W	3000K/4000K/5700K	1,550 lm	>80	>0.9
NLED9508E/NLED9518E 20W	3000K/4000K/5700K	1,950 lm	>80	>0.9
NLED9508E/NLED9518E 25W	3000K/4000K/5700K	2,400 lm	>80	>0.9