

NTLED332 series

Versatile LED spotlights for a wide range of installation conditions



TLED332D (Class I)
(Track mounted)



NTLED332C (Class I)
(Track mounted)



NTLED332Z (Class I)
(Track mounted)



SLED332 (Class I)
(Surface mounted)



SLED332Q (Class II)
(Recessed mounted)



APPLICATIONS

- Retail stores
- Showrooms
- Museums & galleries
- Bars & restaurants

TECHNICAL DETAILS


- COB LED
- Rated life: 30,000 hours

CONSTRUCTION


- Adjustable angle: horizontal 350°, vertical 90°
- Die-cast aluminium housing, powder coated
- Built-in constant current driver included
- For single circuit NVC track, surface and recessed installations

OPTIONS


- **Colour:** Choice of black or semi-white
- **Beam angle:** Choice of 15°, 24° or 36°
- NVC track and accessories, see page 84 and 85




TLED332C




TLED332D



SLED332




TLED332Z




SLED332Q



Model	Colour temp.	Lumens	CRI	PF	Beam angle
NTLED332D 20W	3000K/4000K/5700K	1,100 lm	>90	>0.9	15°/24°/38°
NTLED332D 30W	3000K/4000K/5700K	1,650 lm	>90	>0.9	15°/24°/38°
NTLED332Z 20W	3000K/4000K/5700K	1,100 lm	>90	>0.9	15°/24°/38°
NTLED332Z 30W	3000K/4000K/5700K	1,650 lm	>90	>0.9	15°/24°/38°
NTLED332C 20W	3000K/4000K/5700K	1,100 lm	>90	>0.9	15°/24°/38°
NTLED332C 30W	3000K/4000K/5700K	1,650 lm	>90	>0.9	15°/24°/38°
SLED332Q 20W	3000K/4000K/5700K	1,100 lm	>90	>0.9	15°/24°/38°
SLED332Q 30W	3000K/4000K/5700K	1,650 lm	>90	>0.9	15°/24°/38°
SLED332 20W	3000K/4000K/5700K	1,100 lm	>90	>0.9	15°/24°/38°
SLED332 30W	3000K/4000K/5700K	1,650 lm	>90	>0.9	15°/24°/38°



TLED332D 20W 15°



TLED332D 20W 38°