

NTRLED327 series

Track lights with a simple minimalist design



APPLICATIONS

- Chain stores
- Museums
- Fashion shops
- Showrooms

TECHNICAL DETAILS




- COB LED
- Rated life: 30,000 hours

CONSTRUCTION

- Die-cast aluminium housing
- Powder coated surface treatment
- 30° glare-proof design
- Adjustable angle: horizontal 350°, vertical 90°
- Die-cast aluminium heat sink with air convection design
- Built-in constant current driver included
- For single circuit NVC track

OPTIONS

- **Beam angle:** Choice of 15°, 24° or 36°
- **Body color:** Choice of black or semi white
- **Glare-proof ring colour:** Choice of gold or silver colour
- NVC track and accessories, see page 84 and 85



Model	Colour temp.	Lumens	CRI	PF	Beam angle
NTRLED327A 9W	3000K/3500K/4000K/5700K	700 lm	>90	>0.9	15°/24°/36°
NTRLED327B 15W	3000K/3500K/4000K/5700K	1,050 lm	>90	>0.9	15°/24°/36°
NTRLED327C 24W	3000K/3500K/4000K/5700K	1,700 lm	>90	>0.9	15°/24°/36°
NTRLED327 35W	3000K/3500K/4000K/5700K	2,500 lm	>90	>0.9	15°/24°/36°
NTRLED327D 50W	3000K/3500K/4000K/5700K	3,200 lm	>90	>0.9	15°/24°/36°