

NUWLED4330

Adjustable IP68 underwater lights



APPLICATIONS

- Swimming pools
- Fountains
- Underwater decorations

TECHNICAL DETAILS

- High Power LEDs
- Rated life: 30,000 hours

CONSTRUCTION

- Grade 316 satin finish stainless steel body and bracket
- PC lens
- 5mm thickness tempered glass front cover

OPTIONS


- **Driver:** Choice of separate DC 24V IP65 driver (separate driver not included)




Warning

- Must be installed underwater to prevent over-heating

NUWLED4330 18W 45°



NUWLED4330 36W 15°



Model	Watts	Colour temp.	Lumens	CRI	Beam angle
NUWLED4330 6W	6W	3000K	540 lm	>80	15°/20°/30°/45°
NUWLED4330 6W	6W	6000K	570 lm	>80	15°/20°/30°/45°
NUWLED4330 10W	10W	RGB	/	>80	15°/20°/30°/45°
NUWLED4330 18W	18W	3000K	1,500 lm	>80	15°/20°/30°/45°
NUWLED4330 18W	18W	6000K	1,700 lm	>80	15°/20°/30°/45°
NUWLED4330 22W	22W	RGB	/	>80	15°/20°/30°/45°
NUWLED4330 36W	36W	3000K	2,670 lm	>80	15°/20°/30°/45°
NUWLED4330 36W	36W	6000K	3,050 lm	>80	15°/20°/30°/45°
NUWLED4330 36W	36W	RGB	/	>80	15°/20°/30°/45°

